

Micro Commercial Components



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939 **1SS193**

Features

- Low Leakage Current
- Surface Mount SOT-23 Package
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1
- Marking Code : F3
- Halogen free available upon request by adding suffix "-HF"


Maximum Ratings


Reverse Voltage	V_R	80V
Forward Current	I _F	100mA
Power Dissipation @ T _A =25 ^o C	P _D	150mW
Storage Temperature Range	T_{stg}	-55°C to +150°C
Junction Temperature	Tį	150°C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Reverse Voltage	V_R	80V				
Minimum Reverse	$V_{(BR)}$	80V	I _R =100uA			
Breakdown Voltage			$T_A = 25^{\circ}C$			
Maximum Forward			$T_A = 25^{\circ}C$			
Voltage	V_{F}	1.2V	$I_F = 100 \text{mA};$			
Maximum Reverse						
Voltage Leakage	I _R	0.5uA	V _R =80Volts			
Current			$T_A = 25^{\circ}C$			
. 5.		0.0.5				
Maximum Diode	C_D	3.0pF	Measured at			
Capacitance			f=1.0MHz,			
			V _R =0			
Maximum Reverse	t _{rr}	4.0ns				
Recovery Time						


150mW Switching Diodes





DIMENSIONS					
	INCHES		MM		
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.110	.120	2.80	3.04	
В	.083	.104	2.10	2.64	
С	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
Е	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
Н	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	


Suggested Solder Pad Layout





1SS193



Micro Commercial Components












Fig.1 Reverse recovery time (trr) test circuit

OUTPUT WAVEFORM







Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note: Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.