

**PLUGSERIES**  
**PRS 115Vdc LD 2CO**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com



High power/currents can be safely switched with the PLUGSERIES. The modular system enables conventional relays and LED indicators simply to be plugged in. Retaining and disassembly clips provide a secure mount. Pre-assembled relays with 1 or 2 changeover contacts and input voltages from 24V to 230V round of the product range. Plug-in ZQV 2.5 cross-connectors enable relay multiplexers to be set up quickly thanks to simple side-by-side mounting.

**General ordering data**

Order No.	<a href="#">8536520000</a>
Part designation	PRS 115Vdc LD 2CO
Version	PLUGSERIES, Relays, No. of contacts: 2, CO contact, Rated control voltage: 115 V DC ±10 %, Screw connection
GTIN (EAN)	4032248171668
Qty.	10 pc(s).

## PLUGSERIES PRS 115Vdc LD 2CO

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

## Technical data

### Dimensions

Length	92 mm	Width	15.3 mm
Height	95 mm		

### Temperature

Ambient temperature (operational)	-40 °C...+50 °C	Storage temperature	-40 °C...+85 °C
-----------------------------------	-----------------	---------------------	-----------------

### Input

Rated voltage	300 V AC <sub>eff</sub>	Rated control voltage	115 V DC ±10 %
Pull-in (sparkover) / drop-out voltage DC coil	60 V / 21 V	Rated current DC	6.4 mA
Power rating	740 mW	Status indicator	Green LED

### Output

Continuous current	8 A	Max. switching current	16 A
Sparkover time / Drop-out time	7.7 ms / 13.1 ms	Switch-off delay	<45ms
Switch-on delay	9 ms	Switching voltage AC, max.	250 V
min. switching capacity	10 V / 100 mA		

### Contact data

Contact design	CO contact	No. of contacts	2
Contact material	AgNi 90/10	Mechanical service life	5 x 10 <sup>6</sup> switching cycles

### Rated data

Conductor connection system	Screw connection	DIN Rail compatibility	TS 35
Flammability class UL 94	V-0	Humidity	40°C / 93% rel. humidity, no condensation
Solid, max.	2.5 mm <sup>2</sup>		

### Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	> 8 mm	Impulse withstand voltage	6 kV
Overvoltage category	III	Pollution severity	2
Protection class	IP 20	Protective separation acc. to VDE 0106 part 101	Yes
Rated voltage	300 V AC <sub>eff</sub>		

### Other technical data

Free-wheel diode	No	Reverse polarity protection	No
Status indicator	Green LED	Version	Relay coupler

### Approvals

Approvals institutes	CSA; CURUS; GOSTME25; CE
----------------------	--------------------------

### Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01

Creation date November 15, 2010 8:21:38 PM CET

Last update 27.09.2010 / We reserve the right to make technical changes.

**Datasheet**

**PLUGSERIES  
PRS 115Vdc LD 2CO**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**

**Notes**

Note, technical data

Cross-connectors and markers - refer to PLUGSERIES accessories

**PLUGSERIES**  
**PRS 115Vdc LD 2CO**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Electric symbol**

